Annotated for Statistical Reporting Purposes

SECTION XV

BASE METALS AND ARTICLES OF BASE METAL

XV-1

Notes

- 1. This section does not cover:
 - (a) Prepared paints, inks or other products with a basis of metallic flakes or powder (headings 3207 to 3210, 3212, 3213 or 3215);
 - (b) Ferrocerium or other pyrophoric alloys (heading 3606);
 - (c) Headgear or parts thereof of heading 6506 or 6507;
 - (d) Umbrella frames or other articles of heading 6603;
 - (e) Goods of chapter 71 (for example, precious metal alloys, base metal clad with precious metal, imitation jewelry);
 - (f) Articles of section XVI (machinery, mechanical appliances and electrical goods);
 - (g) Assembled railway or tramway track (heading 8608) or other articles of section XVII (vehicles, ships and boats, aircraft);
 - (h) Instruments or apparatus of section XVIII, including clock or watch springs;
 - (ij) Lead shot prepared for ammunition (heading 9306) or other articles of section XIX (arms and ammunition);
 - (k) Articles of chapter 94 (for example, furniture, mattress supports, luminaires and lighting fittings, illuminated signs, prefabricated buildings);
 - (I) Articles of chapter 95 (for example, toys, games, sports equipment);
 - (m) Hand sieves, buttons, pens, pencil-holders, pen nibs, monopods, bipods, tripods and similar articles or other articles of chapter 96 (miscellaneous manufactured articles); or
 - (n) Articles of chapter 97 (for example, works of art).
- 2. Throughout the tariff schedule, the expression "parts of general use" means:
 - (a) Articles of heading 7307, 7312, 7315, 7317 or 7318 and similar articles of other base metal, other than articles specially designed for use exclusively in implants in medical, surgical, dental or veterinary sciences (heading 9021);
 - (b) Springs and leaves for springs, of base metal, other than clock or watch springs (heading 9114); and
 - (c) Articles of heading 8301, 8302, 8308 or 8310 and frames and mirrors, of base metal, of heading 8306.

In chapters 73 to 76 and 78 to 82 (but not in heading 7315) references to parts of goods do not include references to parts of general use as defined above.

Subject to the preceding paragraph and to note 1 to chapter 83, the articles of chapter 82 or 83 are excluded from chapters 72 to 76 and 78 to 81.

- 3. Throughout the schedule, the expression "base metals" means: iron and steel, copper, nickel, aluminum, lead, zinc, tin, tungsten (wolfram), molybdenum, tantalum, magnesium, cobalt, bismuth, cadmium, titanium, zirconium, antimony, manganese, beryllium, chromium, germanium, vanadium, gallium, hafnium, indium, niobium (columbium), rhenium and thallium.
- 4. Throughout the schedule, the term "<u>cermets</u>" means products containing a microscopic heterogeneous combination of a metallic component and a ceramic component. The term "<u>cermets</u>" includes sintered metal carbides (metal carbides sintered with a metal).
- 5. Classification of alloys (other than ferroalloys and master alloys as defined in chapters 72 and 74):
 - (a) An alloy of base metals is to be classified as an alloy of the metal which predominates by weight over each of the other metals.

Annotated for Statistical Reporting Purposes

XV-2

Notes (con.)

- (b) An alloy composed of base metals of this section and of elements not falling within this section is to be treated as an alloy of base metals of this section if the total weight of such metals equals or exceeds the total weight of the other elements present.
- (c) In this section the term "alloys" includes sintered mixtures of metal powders, heterogeneous intimate mixtures obtained by melting (other than cermets) and intermetallic compounds.
- Unless the context otherwise requires, any reference in the tariff schedule to a base metal includes a reference to alloys which, by virtue of note 5 above, are to be classified as alloys of that metal.
- Classification of composite articles:

Except where the headings otherwise require, articles of base metal (including articles of mixed materials treated as articles of base metal under the General Rules of Interpretation) containing two or more base metals are to be treated as articles of the base metal predominating by weight over each of the other metals. For this purpose:

- (a) Iron and steel, or different kinds of iron or steel, are regarded as one and the same metal;
- (b) An alloy is regarded as being entirely composed of that metal as an alloy of which, by virtue of note 5, it is classified; and
- (c) A cermet of heading 8113 is regarded as a single base metal.
- 8. In this section, the following expressions have the meanings hereby assigned to them:
 - (a) Waste and scrap
 - (i) All metal waste and scrap;
 - (ii) Metal goods definitely not usable as such because of breakage, cutting-up, wear or other reasons.
 - (b) Powders

Products of which 90 percent or more by weight passes through a sieve having a mesh aperture of 1 mm.

9. For the purposes of chapters 74 to 76 and 78 to 81, the following expressions have the meanings hereby assigned to them:

(a) Bars and rods

Rolled, extruded, drawn or forged products, not in coils, which have a uniform solid cross section along their whole length in the shape of circles, ovals, rectangles (including squares), equilateral triangles or regular convex polygons (including "flattened circles" and "modified rectangles", of which two opposite sides are convex arcs, the other two sides being straight, of equal length and parallel). Products with a rectangular (including square), triangular or polygonal cross section may have corners rounded along their whole length. The thickness of such products which have a rectangular (including "modified rectangular") cross section exceeds one-tenth of the width. The expression also covers cast or sintered products, of the same forms and dimensions, which have been subsequently worked after production (otherwise than by simple trimming or de-scaling), provided that they have not thereby assumed the character of articles or products of other headings.

Wire bars and billets of chapter 74 with their ends tapered or otherwise worked simply to facilitate their entry into machines for converting them into, for example, drawing stock (wire rod) or tubes, are however to be taken to be unwrought copper of heading 7403. This provision applies *mutatis mutandis* to the products of chapter 81.

(b) Profiles

Rolled, extruded, drawn, forged or formed products, coiled or not, of a uniform cross section along their whole length, which do not conform to any of the definitions of bars, rods, wire, plates, sheets, strip, foil, tubes or pipes. The expression also covers cast or sintered products, of the same forms, which have been subsequently worked after production (otherwise than by simple trimming or de-scaling), provided that they have not thereby assumed the character of articles or products of other headings.

(c) Wire

Rolled, extruded or drawn products, in coils, which have a uniform solid cross section along their whole length in the shape of circles, ovals, rectangles (including squares), equilateral triangles or regular convex polygons (including "flattened circles" and "modified rectangles", of which two opposite sides are convex arcs, the other two sides being straight, of equal length and parallel). Products with a rectangular (including square), triangular or polygonal cross section may have corners rounded along their whole

Annotated for Statistical Reporting Purposes

XV-3

Notes (con.)

length. The thickness of such products which have a rectangular (including "modified rectangular") cross section exceeds one-tenth of the width.

(d) Plates, sheets, strip and foil

Flat-surfaced products (other than the unwrought products), coiled or not, of solid rectangular (other than square) cross section with or without rounded corners (including "modified rectangles" of which two opposite sides are convex arcs, the other two sides being straight, of equal length and parallel) of a uniform thickness, which are:

- -of rectangular (including square) shape with a thickness not exceeding one-tenth of the width;
- -of a shape other than rectangular or square, of any size, provided that they do not assume the character of articles or products of other headings.

Headings for plates, sheets, strip, and foil apply, *inter alia*, to plates, sheets, strip, and foil with patterns (for example, grooves, ribs, checkers, tears, buttons, lozenges) and to such products which have been perforated, corrugated, polished or coated, provided that they do not thereby assume the character of articles or products of other headings.

(e) Tubes and pipes

Hollow products, coiled or not, which have a uniform cross section with only one enclosed void along their whole length in the shape of circles, ovals, rectangles (including squares), equilateral triangles or regular convex polygons, and which have a uniform wall thickness. Products with a rectangular (including square), equilateral triangular or regular convex polygonal cross section, which may have corners rounded along their whole length, are also to be considered as tubes and pipes provided the inner and outer cross sections are concentric and have the same form and orientation. Tubes and pipes of the foregoing cross sections may be polished, coated, bent, threaded, drilled, waisted, expanded, cone-shaped or fitted with flanges, collars or rings.

Additional U.S. Note

1. For the purposes of this section, the term "unwrought" refers to metal, whether or not refined, in the form of ingots, blocks, lumps, billets, cakes, slabs, pigs, cathodes, anodes, briquettes, cubes, sticks, grains, sponge, pellets, flattened pellets, rounds, rondelles, shot and similar manufactured primary forms, but does not cover rolled, forged, drawn or extruded products, tubular products or cast or sintered forms which have been machined or processed otherwise than by simple trimming, scalping or descaling.

Annotated for Statistical Reporting Purposes

CHAPTER 72

IRON AND STEEL

XV 72-1

Notes

 In this chapter and, in the case of notes (d), (e) and (f) below throughout the tariff schedule, the following expressions have the meanings hereby assigned to them:

(a) Pig iron

Iron-carbon alloys not usefully malleable, containing more than 2 percent by weight of carbon and which may contain by weight one or more other elements within the following limits:

- not more than 10 percent of chromium
- not more than 6 percent of manganese
- not more than 3 percent of phosphorus
- not more than 8 percent of silicon
- a total of not more than 10 percent of other elements.

(b) Spiegeleisen

Iron-carbon alloys containing by weight more than 6 percent but not more than 30 percent of manganese and otherwise conforming to the specification at (a) above.

(c) Ferroalloys

Alloys in pigs, blocks, lumps or similar primary forms, in forms obtained by continuous casting and also in granular or powder forms, whether or not agglomerated, commonly used as an additive in the manufacture of other alloys or as deoxidants, desulfurizing agents or for similar uses in ferrous metallurgy and generally not usefully malleable, containing by weight 4 percent or more of the element iron and one or more of the following:

- more than 10 percent of chromium
- more than 30 percent of manganese
- more than 3 percent of phosphorus
- more than 8 percent of silicon
- a total of more than 10 percent of other elements, excluding carbon, subject to a maximum content of 10 percent in the case of copper.

(d) Steel

Ferrous materials other than those of heading 7203 which (with the exception of certain types produced in the form of castings) are usefully malleable and which contain by weight 2 percent or less of carbon. However, chromium steels may contain higher proportions of carbon.

(e) Stainless steel

Alloy steels containing, by weight 1.2 percent or less of carbon and 10.5 percent or more of chromium, with or without other elements.

Annotated for Statistical Reporting Purposes

XV 72-2 <u>Notes</u> (con.)

(f) Other alloy steel

Steels not complying with the definition of stainless steel and containing by weight one or more of the following elements in the proportion shown:

- 0.3 percent or more of aluminum
- 0.0008 percent or more of boron
- 0.3 percent or more of chromium
- 0.3 percent or more of cobalt
- 0.4 percent or more of copper
- 0.4 percent or more of lead
- 1.65 percent or more of manganese
- 0.08 percent or more of molybdenum
- 0.3 percent or more of nickel
- 0.06 percent or more of niobium
- 0.6 percent or more of silicon.
- 0.05 percent or more of titanium
- 0.3 percent or more of tungsten (wolfram)
- 0.1 percent or more of vanadium
- 0.05 percent or more of zirconium
- 0.1 percent or more of other elements (except sulfur, phosphorus, carbon and nitrogen), taken separately.

(g) Remelting scrap ingots of iron or steel

Products roughly cast in the form of ingots without feeder-heads or hot tops, or of pigs, having obvious surface faults and not complying with the chemical composition of pig iron, spiegeleisen or ferroalloys.

(h) Granules

Products of which less than 90 percent by weight passes through a sieve with a mesh aperture of 1 mm and of which 90 percent or more by weight passes through a sieve with a mesh aperture of 5 mm.

(ij) Semifinished products

Continuous cast products of solid section, whether or not subjected to primary hot-rolling; and

Other products of solid section, which have not been further worked than subjected to primary hot-rolling or roughly shaped by forging, including blanks for angles, shapes or sections.

These products are not presented in coils.

Annotated for Statistical Reporting Purposes

Notes (con.)

(k) Flat-rolled products

Rolled products of solid rectangular (other than square) cross section, which do not conform to the definition at (ij) above in the form of:

- coils of successively superimposed layers, or
- straight lengths, which if of a thickness less than 4.75 mm are of a width measuring at least 10 times the thickness or if of a thickness of 4.75 mm or more are of a width which exceeds 150 mm and measures at least twice the thickness.

Flat-rolled products include those with patterns in relief derived directly from rolling (for example, grooves, ribs, checkers, tears, buttons, lozenges) and those which have been perforated, corrugated or polished, provided that they do not thereby assume the character of articles or products of other headings.

Flat-rolled products of a shape other than rectangular or square, of any size, are to be classified as products of a width of 600 mm or more, provided that they do not assume the character of articles or products of other headings.

(I) Bars and rods, hot-rolled, in irregularly wound coils

Hot-rolled products in irregularly wound coils, which have a solid cross section in the shape of circles, segments of circles, ovals, rectangles (including squares), triangles or other convex polygons (including "flattened circles" and "modified rectangles", of which two opposite sides are convex arcs, the other two sides being straight, of equal length and parallel). These products may have indentations, ribs, grooves or other deformations produced during the rolling process (reinforcing bars and rods).

(m) Other bars and rods

Products which do not conform to any of the definitions at (ij), (k) or (l) above or to the definition of wire, which have a uniform solid cross section along their whole length in the shape of circles, segments of circles, ovals, rectangles (including squares), triangles or other convex polygons (including "flattened circles" and "modified rectangles", of which two opposite sides are convex arcs, the other two sides being straight, of equal length and parallel). These products may:

- have indentations, ribs, grooves or other deformations produced during the rolling process (reinforcing bars and rods);
- be twisted after rolling.

(n) Angles, shapes and sections

Products having a uniform solid cross section along their whole length which do not conform to any of the definitions at (ij), (k), (l) or (m) above or to the definition of wire.

Chapter 72 does not include products of heading 7301 or 7302.

(o) Wire

Cold-formed products in coils, of any uniform solid cross section along their whole length, which do not conform to the definition of flat-rolled products.

(p) Hollow drill bars and rods

Hollow bars and rods of any cross section, suitable for drills, of which the greatest external dimension of the cross section exceeds 15 mm but does not exceed 52 mm, and of which the greatest internal dimension does not exceed one half of the greatest external dimension. Hollow bars and rods of iron or steel not conforming to this definition are to be classified in heading 7304.

- 2. Ferrous metals clad with another ferrous metal are to be classified as products of the ferrous metal predominating by weight.
- 3. Iron or steel products obtained by electrolytic deposition, by pressure casting or by sintering are to be classified according to their form, their composition and their appearance, in the headings of this chapter appropriate to similar hot-rolled products.

Subheading Notes

1. In this chapter the following expressions have the meanings hereby assigned to them:

Annotated for Statistical Reporting Purposes

XV 72-4

Subheading Notes (con.)

(a) Alloy pig iron

Pig iron containing, by weight, one or more of the following elements in the specified proportions:

- more than 0.2 percent of chromium
- more than 0.3 percent of copper
- more than 0.3 percent of nickel
- more than 0.1 percent of any of the following elements: aluminum, molybdenum, titanium, tungsten (wolfram), vanadium.

(b) Nonalloy free-cutting steel

Nonalloy steel containing by weight one or more of the following elements in the specified proportions:

- 0.08 percent or more of sulfur
- 0.1 percent or more of lead
- more than 0.05 percent of selenium
- more than 0.01 percent of tellurium
- more than 0.05 percent of bismuth.

(c) Silicon electrical steel

Alloy steels containing by weight at least 0.6 percent but not more than 6 percent of silicon and not more than 0.08 percent of carbon. They may also contain by weight not more than 1 percent of aluminum but no other element in a proportion that would give the steel the characteristics of another alloy steel.

(d) High-speed steel

Alloy steels containing, with or without other elements, at least two of the three elements molybdenum, tungsten and vanadium with a combined content by weight of 7 percent or more, 0.6 percent or more of carbon and 3 to 6 percent of chromium.

(e) Silico-manganese steel

Alloy steels containing by weight:

- not more than 0.7 percent of carbon,
- 0.5 percent or more but not more than 1.9 percent of manganese, and
- 0.6 percent or more but not more than 2.3 percent of silicon, but no other element in a proportion that would give the steel the characteristics of another alloy steel.
- 2. For the classification of ferroalloys in the subheadings of heading 7202 the following rule should be observed:

A ferroalloy is considered as binary and classified under the relevant subheading (if it exists) if only one of the alloy elements exceeds the minimum percentage laid down in chapter note 1(c); by analogy, it is considered respectively as ternary or quaternary if two or three alloy elements exceed the minimum percentage.

For the application of this rule, the unspecified "other elements" referred to in chapter note 1(c) must each exceed 10 percent by weight.

Additional U.S. Notes

- 1. For the purposes of the tariff schedule the following expressions have the meanings hereby assigned to them:
 - (a) High-strength steel

Flat-rolled products of a thickness of less than 3 mm and having a minimum yield point of 275 MPa or of a thickness of 3 mm or more and having a minimum yield point of 355 MPa.

Annotated for Statistical Reporting Purposes

Additional U.S. Notes (con.)

(b) Universal mill plate

Flat-rolled products rolled on four faces or in a closed box pass, of a width exceeding 150 mm but not exceeding 1,250 mm and of thickness of not less than 4 mm, not in coils and without patterns in relief.

(c) Concrete reinforcing bars and rods

Hot-rolled bars and rods containing indentations, ribs, grooves or other deformations produced during the rolling process or twisted after rolling.

(d) Razor blade steel

Flat-rolled products of stainless steel not over 0.25 mm in thickness and not over 23 mm in width, and containing by weight not over 14.7 percent of chromium, certified at the time of entry to be used in the manufacture of razor blades.

(e) Tool steel

Alloy steels which contain the following combinations of elements in the quantity by weight respectively indicated:

- (i) more than 1.2 percent carbon and more than 10.5 percent chromium; or
- (ii) not less than 0.3 percent carbon and 1.25 percent or more but less than 10.5 percent chromium; or
- (iii) not less than 0.85 percent carbon and 1 percent to 1.8 percent, inclusive, manganese; or
- (iv) 0.9 percent to 1.2 percent, inclusive, chromium and 0.9 percent to 1.4 percent, inclusive, molybdenum; or
- (v) not less than 0.5 percent carbon and not less than 3.5 percent molybdenum; or
- (vi) not less than 0.5 percent carbon and not less than 5.5 percent tungsten.

(f) Chipper knife steel

Alloy tool steels which contain, in addition to iron, each of the following elements by weight in the amount specified:

- (i) not less than 0.48 nor more than 0.55 percent of carbon;
- (ii) not less than 0.2 nor more than 0.5 percent of manganese;
- (iii) not less than 0.75 nor more than 1.05 percent of silicon;
- (iv) not less than 7.25 nor more than 8.75 percent of chromium;
- (v) not less than 1.25 nor more than 1.75 percent of molybdenum;
- (vi) none, or not more than 1.75 percent of tungsten; and
- (vii) not less than 0.2 nor more than 0.55 percent of vanadium.

(g) Heat-resisting steel

Alloy steels containing by weight less than 0.3 percent of carbon and 4 percent or more but less than 10.5 percent of chromium.

(h) Ball-bearing steel

Alloy tool steels which contain, in addition to iron, each of the following elements by weight in the amount specified:

- (i) not less than 0.95 nor more than 1.13 percent of carbon;
- (ii) not less than 0.22 nor more than 0.48 percent of manganese;
- (iii) none, or not more than 0.03 percent of sulfur;
- (iv) none, or not more than 0.03 percent of phosphorus;

Annotated for Statistical Reporting Purposes

XV 72-6

Additional U.S. Notes (con.)

- (v) not less than 0.18 nor more than 0.37 percent of silicon;
- (vi) not less than 1.25 nor more than 1.65 percent of chromium;
- (vii) none, or not more than 0.28 percent of nickel;
- (viii) none, or not more than 0.38 percent of copper; and
- (ix) none, or not more than 0.09 percent of molybdenum.
- 2. For the purposes of this chapter, unless the context provides otherwise, the term "further worked" refers to products subjected to any of the following surface treatments: polishing and burnishing; artificial oxidation; chemical surface treatments such as phosphatizing, oxalating and borating; coating with metal; coating with nonmetallic substances (e.g., enameling, varnishing, lacquering, painting, coating with plastics materials); or cladding.
- 3. No allowance or reduction of duties for partial damage or loss in consequence of discoloration or rust occurring before entry shall be made upon iron or steel or upon any article of iron or steel.

Statistical Notes

- For the purposes of the tariff schedule, the expression <u>high-nickel alloy steel</u> refers to alloy steel containing by weight 24 percent or more of nickel, with or without other elements.
- 2. For the purposes of subheading 7204.10, <u>waste and scrap of cast iron</u> includes but is not necessarily limited to: cupola cast (ISRI number 252); charging box cast (ISRI number 253); heavy breakable cast (ISRI number 254); hammer blocks or bases (ISRI number 255); burnt iron (ISRI number 256); mixed cast (ISRI number 257); stove plate, clean cast iron stove (ISRI number 258); clean auto cast (ISRI numbers 259, 262 and 263); motor blocks (ISRI number 260); drop broken machinery cast (ISRI number 261); malleable (ISRI number 264); ingot molds and stools (ISRI numbers 265 and 266); and railroad ferrous scrap consisting of cast iron No. 1, No. 2, No. 3 and No. 4, cast iron brake shoes and No. 1 wheels.
- 3. For the purposes of subheading 7204.41 or 7204.49 the expression:
 - (a) No. 1 heavy melting includes, but is not necessarily limited to:
 - No. 1 heavy melting steel (ISRI numbers 200, 201 and 202); bundled No. 1 steel (ISRI number 217); cast steel (ISRI number 233); springs and crankshafts (ISRI number 244); ship scrap; and railroad ferrous scrap consisting of cast steel No. 1 and No. 2, railroad No. 1 melting steel, spring steel, destroyed steel cars, destroyed steel car sides and box car roofs (note: other types of railroad ferrous scrap are included in some of the grades listed below);
 - (b) No. 2 heavy melting includes, but is not necessarily limited to:
 - No. 2 heavy melting steel (ISRI numbers 203, 204, 205 and 206); bundled No. 2 steel (ISRI number 218); foundry steel (ISRI numbers 242 and 243); and hard steel cut 76 cm and under (ISRI number 248);
 - (c) No. 1 bundles includes, but is not necessarily limited to:
 - No. 1 busheling (ISRI number 207); new black sheet clippings (ISRI number 207A); No. 1 bundles (ISRI number 208); electric furnace bundles (ISRI number 235); silicon-bearing steel busheling, clippings, and bundles (ISRI numbers 239, 240 and 250); No. 1 railroad ferrous sheet scrap; and car clips;
 - (d) $\underline{\text{No. 2 bundles}}$ includes, but is not necessarily limited to:
 - No. 2 bundles (ISRI number 209); No. 3 bundles (ISRI number 214); incinerator bundles (ISRI number 215); terne plate bundles (ISRI number 216); and auto slabs (ISRI numbers 224 and 225);
 - (e) Borings, shovelings and turnings includes, but it not necessarily limited to:

Machine shop turnings, shoveling turnings and iron borings (ISRI numbers 219, 220, 221, 222 and 223); briquetted iron borings (ISRI number 226); briquetted steel turnings (ISRI number 227); alloy free turnings (ISRI numbers 245, 246 and 247); heavy turnings (ISRI number 251); chemical borings, No. 1 and No. 2 (ISRI numbers 267 and 271); malleable borings (ISRI number 270); steel shavings; and railroad ferrous scrap consisting of No. 1 turnings and No. 2 turnings, drillings and/or borings:

Annotated for Statistical Reporting Purposes

XV 72-7

Statistical Notes (con.)

(f) Shredded scrap includes, but is not necessarily limited to:

Shredded clippings (ISRI number 212); and shredded automobile scrap (ISRI numbers 210 and 211);

(g) Cut plate and structural includes but is not necessarily limited to:

Billet, bloom and forge crops (ISRI number 229); bar crops, punchings and plate scrap (ISRI numbers 230 and 234); plate and structural (ISRI numbers 231, 232, 236, 237 and 238); chargeable ingots and ingot butts (ISRI number 241); and chargeable slab crops (ISRI number 249).

- 4. (a) "Advanced" high strength steel refers to flat-rolled products of a thickness of less than 3 mm that meet the definition of high-strength steel in Additional U.S. Note 1(a) to chapter 72 and have a minimum tensile strength of 590 MPa or more but less than 980 MPa. "Ultra" high-strength steel refers to flat-rolled products of a thickness of less than 3 mm that meet the definition of high-strength steel in Additional U.S. Note 1(a) to chapter 72 and have a minimum tensile strength of 980 MPa or more.
 - (b) "Other" high-strength steel refers to flat-rolled products of a thickness of less than 3 mm that meet the definition of high-strength steel in Additional U.S. Note 1(a) to chapter 72 and have a minimum tensile strength of less than 590 MPa.

5. Tire cord-quality steel wire rod

Rod measuring 5.0 mm or more but not more than 6.0 mm in cross-sectional diameter, with an average partial decarburization of no more than 70 micrometers in depth (maximum 200 micrometers); having no non-deformable inclusions with a thickness (measured perpendicular to the rolling direction) greater than 20 micrometers; and, containing by weight the following elements in proportions:

- 0.68 percent or more carbon,
- less than 0.01 percent of aluminum,
- 0.040 percent or less, in aggregate, of phosphorus and sulfur,
- 0.008 percent or less of nitrogen, and
- not more than 0.55 percent, in the aggregate, of copper, nickel and chromium.

6. Cold Heading Quality (CHQ)

Rod suitable for cold heading, forging, or thread rolling, and meeting standard ASTM F2282.

7. Welding quality wire rod

Rod measuring less than 10 mm in diameter having less than 0.2 percent carbon, less than 0.04 percent sulfur, and less than 0.04 percent phosphorus, suitable for drawing or rolling to final size for use as:

- (i) an uncoated or plated or copper coated solid welding wire or rod;
- (ii) the core wire or core rod for covered shielded metal arc ("SMAW") welding electrode, or
- (iii) the formed jacket of a flux cored welding electrode

that is suitable for consumption in the electric arc welding process.

Spring round wire

For the purposes of statistical reporting number 7223.00.1005, the term "spring round wire" means wire suitable for the manufacture of springs and meeting ASTM standard A313.

Compiler's Note

The provisions of subchapter II of chapter 99 (Miscellaneous Tariff Bills or MTBs), the provisions of the Generalized System of Preferences (GSP) found in General Note 4 and most product exclusions from the additional tariffs on products of China in subchapter III of chapter 99 expired on December 31, 2020. However, no endnotes or footnotes relating to these provisions have been deleted as of the issue date of this edition.

Heading/ Subheading	Stat. Suf-	Article Description	Article Description Unit Rates of Duty of 1				Rates of Duty 1	
Subfricading	fix	/ Hadio Boodiphon	Quantity	General	Special			
		I. PRIMARY MATERIALS; PRODUCTS IN GRANULAR OR POWDER FORM						
201 201.10.00		Pig iron and spiegeleisen in pigs, blocks or other primary forms: Nonalloy pig iron containing by weight 0.5 percent or less of phosphorus	t	Free ^{1/}		\$1.11/t		
201.20.00	00	Nonalloy pig iron containing by weight more than 0.5 percent of phosphorus				\$1.11/t		
201.50 201.50.30	00	Alloy pig iron; spiegeleisen: Alloy pig iron	t	Free ^{1/}		\$1.11/t		
201.50.60 202	00	SpiegeleisenFerroalloys:	t	Free ^{1/}		0.5%		
'202.11 '202.11.10	00	Ferromanganese: Containing by weight more than 2 percent of carbon: Containing by weight more than 2 percent but not more than 4 percent of carbon	kg	1.4% ^{1/}	Free (A*, AU, BH,	6.5%		
			Mn kg		CL, CO, D, E, IL, JO, KR, MA, OM, P, PA, PE, S, SG)			
202.11.50	00	Containing by weight more than 4 percent of	L	1/	Free (A. All Bli	10.50/		
		carbon	Kg Mn kg	1.5%"	Free (A+, AU, BH, CL, CO, D, E, IL, JO, KR, MA, OM, P, PA, PE, S, SG)	10.5%		
'202.19 '202.19.10	00	Other: Containing by weight not more than 1 percent of carbon	kg	2 29/ 1/	Free (A, AU, BH, CL,	22%		
			Mn kg	2.3 /0	CO, D, E, IL, JO, KR, MA, OM, P, PA, PE, S, SG)	22,0		
'202.19.50	00	Containing by weight more than 1 percent but not more than 2 percent of carbon	kg Mn kg	1.4% ^{1/}	Free (A, AU, BH, CL, CO, D, E, IL, JO, KR, MA, OM, P, PA, PE, S, SG)	6.5%		

	>	(٧
7	2	_	c

	Stat. Suf-	Article Description	Unit		Rates of Duty	2
Subheading	Sut- fix	Article Description	of Quantity	General	1 Special	2
'202 (con.)		Ferroalloys: (con.)				
` /		Ferrosilicon:				
'202.21		Containing by weight more than 55 percent of silicon:				
		Containing by weight more than 55 percent but not				
7000 01 10	00	more than 80 percent of silicon:				
202.21.10	00	Containing by weight more than 3 percent of calcium	kg	4 40/1/	Free (A*, AU, BH,	11.5%
		calcium	Si kg	1.1%	CL, CO, D, E, IL,	11.570
			o. ng		JO, KR, MA, OM,	
					P, PA, PE, S, SG)	
202.21.50	00	Other	kg	1 5% 1/	Free (A*, AU, BH,	11.5%
			Si kg	1.070	CL, CO, D, E, IL,	
					JO, KR, MA, OM,	
					P, PA, PE, S, SG)	
202.21.75	00	Containing by weight more than 80 percent but not		47	- /A ALL DIL	00/
		more than 90 percent of silicon	kg Si kg	1.9% ^{1/}	Free (A+, AU, BH,	9%
			Sirky		CL, CO, D, E, IL, JO, KR, MA, OM,	
					P, PA, PE, S, SG)	
202.21.90	٥٥	Containing by weight more than 90 percent of			.,,, 0, 00,	
202.21.30	00		kg	E 90/ 1/	Free (A+, AU, BH,	40%
			Si kg	3.0%	CL, CO, D, E, IL,	10 70
			J		JO, KR, MA, OM,	
					P, PA, PE, S, SG)	
202.29.00		Other		Free ^{1/}		4.4¢/kg on
						silicon content
	10	Containing by weight over 2 percent of				content
	10		kg			
			Si kg			
	50	Other	kg			
	00	G1101	Si kg			
202.30.00	00	Ferrosilicon manganese	kg	3.9% ^{1/}	Free (A*, AU, BH,	23%
			Mn kg		CL, CO, D, E, IL,	
					JO, KR, MA, OM,	
					P, PA, PE, S, SG)	

	Stat. Suf-	Article Description	Unit of		Rates of Duty 1	2
	fix	<u> </u>	Quantity	General	Special	<u> </u>
202 (con.)		Ferroalloys: (con.)				
202 44 22	00	Ferrochromium:	le m	1 22/1/	Free (A* All Dil	7.50/
202.41.00	00	Containing by weight more than 4 percent of carbon		1.9% "	Free (A*, AU, BH,	7.5%
			Cr kg		CL, CO, D, E, IL,	
					JO, KR, MA, OM,	
					P, PA, PE, S, SG)	
202.49		Other:				
202.49.10	00	Containing by weight more than 3 percent of				
		carbon	kg	1.9% ^{1/}	Free (A+, AU, BH,	7.5%
			Cr kg		CL, CO, D, E, IL,	
					JO, KR, MA, OM,	
					P, PA, PE, S, SG)	
202.49.50		Other		3.1% ^{1/}	Free (A, AU, BH, CL,	30%
					CO, D, E, IL, JO,	
					KR, MA, OM, P,	
	, [PA, PE, S, SG)	
	10	Containing by weight more than 0.5 percent].			
		of carbon	kg			
			Cr kg			
	90	Other	kg			
			Cr kg			
202.50.00	00	Ferrosilicon chromium	kg	10% ^{1/}	Free (A, AU, BH, CL,	25%
			Cr kg		CO, D, E, IL, JO,	
					KR, MA, OM, P,	
					PA, PE, S, SG)	
202.60.00	00	Ferronickel	kg	Free		6.6¢/kg
·			Ni kg			
202.70.00	00	Ferromolybdenum	ka	4 5%	Free (A+, AU, BH,	31.5%
202.70.00	00		Mo kg	7.5 /6	CL, CO, D, E, IL,	31.370
			o ng		JO, KR, MA, OM,	
					P, PA, PE, S, SG)	
200 00 00	00	Ferrotungsten and ferrosilicon tungsten	ka	5.00/1/	•	250/
202.80.00	00	Ferrotungsten and terrosilicon tungsten	Kg	5.6% "	Free (A, AU, BH, CL,	35%
			W kg		CO, D, E, IL, JO,	
					KR, MA, OM, P,	
					PA, PE, S, SG)	
	ı					

	Х	V
72	-1	1

	Stat.	Articla Description	Unit		Rates of Duty	2
Subheading	Suf- fix	Article Description	of Quantity	General	1 Special	2
202 (con.)		Ferroalloys: (con.)				
202.91.00	00	Other: Ferrotitanium and ferrosilicon titanium	l. m	0.70/1/	Free /A . All Dil	050/
202.91.00	00		J	3.7%	Free (A+, AU, BH, CL, CO, D, E, IL, JO, KR, MA, OM, P, PA, PE, S, SG)	25%
202.92.00	00	Ferrovanadium	kg V kg	· 4.2% ^{1/}	Free (A+, AU, BH, CL, CO, E, IL, JO, KR, MA, OM, P, PA, PE, S, SG)	25%
202.93 202.93.40	00	Ferroniobium: Containing by weight less than 0.02 percent of phosphorus or sulfur or less than 0.4 percent of		50/	- (A AU BU	050/
		silicon	kg	. 5%	Free (A+, AU, BH, CL, CO, D, E, IL, JO, KR, MA, OM, P, PA, PE, S, SG)	25%
202.93.80	00	Other	kg	. 5%	Free (A*, AU, BH, CL, CO, D, E, IL, JO, KR, MA, OM,	25%
2000 00		Othory			P, PA, PE, S, SG)	
202.99 202.99.10	00	Other: Ferrozirconium	ka	4.2% ^{1/}	Free (A*, AU, BH,	25%
				4.2 70	CL, CO, D, E, IL, JO, KR, MA, OM, P, PA, PE, S, SG)	
'202.99.20	00	Calcium silicon	kg	· 5% ^{1/}	Free (A, AU, BH, CL, CO, D, E, IL, JO, KR, MA, OM, P, PA, PE, S, SG)	25%
'202.99.80		Other		5% ^{2/}	Free (A+, AU, BH, CL, CO, D, E, IL, JO, KR, MA, OM,	25%
	20	Ferrophosphorus	ka		P, PA, PE, S, SG)	
	40	Other	_			
'203		Ferrous products obtained by direct reduction of iron ore and other spongy ferrous products, in lumps, pellets or similar forms; iron having a minimum purity by weight of 99.94 percent, in lumps, pellets or similar forms:				
203.10.00	00	Ferrous products obtained by direct reduction of iron				
		ore				\$2.21/t
203.90.00	00	Other	t	· Free ^{1/}		\$2.21/t

Heading/ Subheading	Stat. Suf-	Article Description	Unit of	-	Rates of Duty 1	2
	fix		Quantity	General	Special	
204		Ferrous waste and scrap; remelting scrap ingots of iron or steel:				
204.10.00	00	Waste and scrap of cast iron	t	Free ^{1/}		74¢/t
		Waste and scrap of alloy steel:				
204.21.00	00	Of stainless steel	t	Free ^{1/}		74¢/t
204.29.00	00	Other	t	Free ^{1/}		74¢/t
204.30.00	00	Waste and scrap of tinned iron or steel	t	Free ^{1/}		Free
'204.41.00		Other waste and scrap: Turnings, shavings, chips, milling waste, sawdust, filings, trimmings and stampings, whether or not in bundles		Free ¹ ∕		74¢/t
	20	No. 1 bundles				
	40	No. 2 bundles				
	60	Borings, shovelings and turnings				
204.49.00	80	OtherOther		E1/		74¢/t
۷۳.49.00 مے	20	No. 1 heavy melting		⊢ree "		/ 4 ¢/l
	40	No. 2 heavy melting				
		Other:	·			
	60	Cut plate and structural	t			
	70	Shredded	t			
	80	Other				
204.50.00	00	Remelting scrap ingots		Free ^{1/}		74¢/t
205 205.10.00	00	Granules and powders, of pig iron, spiegeleisen, iron or steel: Granules	ka	Froo ^{1/}		3%
		Powders:		1166		
205.21.00	00	Of alloy steel	kg	Free ^{1/}		45%
205.29.00	00	Other				\$2.21/t
				1100		

	Χ	V
72	-1	3

	Stat.		Unit		Rates of Duty	
	Suf- fix	Article Description	of Quantity	General	1 Special	2
		# IDON 4115 1121111 211 2		Joholai	Оросіаі	
		II. IRON AND NONALLOY STEEL				
206		Iron and nonalloy steel in ingots or other primary forms				
206.10.00	00	(excluding iron of heading 7203): Ingots	kg	Free ^{3/}		20%
206.90.00		Other				20%
207		Semifinished products of iron or nonalloy steel:		1100		
207.11.00	00	Containing by weight less than 0.25 percent of carbon: Of rectangular (including square) cross section, the				
207.11.00	00	width measuring less than twice the thickness	kg	Free ^{3/}		20%
207.12.00		Other, of rectangular (other than square) cross				
		section		Free ^{3/}		20%
	10	Having a width measuring less than four times the thickness				
	50	Having a width measuring at least four times the	Ng			
		thickness				
207.19.00	30	Other Of circular cross section		Free ^{3/}		20%
	90	Other	J			
207.20.00	90	Containing by weight 0.25 percent or more of carbon		Free ^{3/}		20%
		Of rectangular (including square) cross section:				
	25	Having a width measuring less than four times the thickness				
	45	Having a width measuring at least four times the	Ng			
		thickness				
	75	Of circular cross section	•			
	90	Other	kg			

Subheading	Suf-	Article Description	of		1	2
	fix		Quantity	General	Special	_
7208		Flat-rolled products of iron or nonalloy steel, of a width of 600 mm or more, hot-rolled, not clad, plated or coated:				
7208.10		In coils, not further worked than hot-rolled, with patterns in relief:				
7208.10.15	00	Pickled Other:	kg	Free ^{3/}		0.4¢/kg + 209
7208.10.30	00	Of a thickness of 4.75 mm or more				20%
7208.10.60	00	Of a thickness of less than 4.75 mm		· Free ^{3/}		20%
7208.25	00	Other, in coils, not further worked than hot-rolled, pickled: Of a thickness of 4.75 mm or more: Of high-strength steel				000/
7208.25.30						20%
7208.25.60	00	Other	kg	Free ^{3/}		0.4¢/kg + 20%
7208.26.00		Of a thickness of 3 mm or more but less than 4.75 mm		Free ^{3/}		0.4¢/kg + 20%
	30	High-strength steel	_			
7208.27.00	60	OtherOf a thickness of less than 3 mm		Free ^{3/}		0.4¢/kg + 20%
	40	High-strength steel: "Advanced" or "ultra" of a kind described in				
		statistical note 4 to this chapter	kg			
	45	Other				
	60	Other	kg			
7208.36.00		Other, in coils, not further worked than hot-rolled: Of a thickness exceeding 10 mm		Free ^{3/}		20%
200.00.00	30	High-strength steel		Free		2070
	60	Other	_			
7208.37.00	00	Of a thickness of 4.75 mm or more but not exceeding 10 mm		Free ^{3/}		20%
	30	High-strength steel		1100		
	60	Other	_			
7208.38.00		Of a thickness of 3 mm or more but less than 4.75 mm		Free ^{3/}		20%
	15	High-strength steel	kg			
		Other:				
	30	With untrimmed edges	kg			
	90	Other	kg			
7208.39.00		Of a thickness of less than 3 mm High-strength steel:		Free ^{3/}		20%
	20	"Advanced" or "ultra" of a kind described in statistical note 4 to this chapter	ka			
	٥.	'	ľ			
	25	Other:Other:	кд			
	30	With untrimmed edges	kg			
	90	Other	_			
				1		

	×	(١
72.		1	ı

	Stat.	Australia Danasadustasa	Unit		Rates of Duty	
	Suf- fix	Article Description	of Quantity	General	1 Special	2
208 (con.)		Flat-rolled products of iron or nonalloy steel, of a width of			ороски.	
, ,		600 mm or more, hot-rolled, not clad, plated or coated: (con.)				
208.40		Not in coils, not further worked than hot-rolled, with patterns				
		in relief:				
208.40.30		Of a thickness of 4.75 mm or more		Free ^{3/}		20%
	30	Of a thickness exceeding 10 mm	kg			
	60	Other				
208.40.60		Of a thickness of less than 4.75 mm		Free ^{3/}		20%
	30	Of a thickness less than 3 mm	kg			
	60	Other	kg			
		Other, not in coils, not further worked than hot-rolled:				
208.51.00		Of a thickness exceeding 10 mm		Free ^{3/}		20%
	30	Universal mill plate	kg			
		Other:				
	45	Of high-strength steel	ka			
		Other	_			
	60 00	Of a thickness of 4.75 mm or more but not exceeding				
200.32.00	00	10 mm	ka	Fran ^{3/}		20%
			Kg	Free-		20 /6
208.53.00	00	Of a thickness of 3 mm or more but less than		2.		
		4.75 mm	kg	Free ^{3/}		20%
208.54.00	00	Of a thickness of less than 3 mm	kg	Free ^{3/}		20%
208.90.00	00	Other	_			20%
209	00	Flat-rolled products of iron or nonalloy steel, of a width of		riee		2070
203		600 mm or more, cold-rolled (cold-reduced), not clad, plated				
		or coated:				
		In coils, not further worked than cold-rolled (cold-reduced):				
209.15.00	00	Of a thickness of 3 mm or more	kg	Free ^{3/}		0.4 c/kg + 20
209.16.00		Of a thickness exceeding 1 mm but less than 3 mm		– 3/		0.4¢/kg + 20
209.10.00				Free=		0.4¢/kg + 20
		Of high-strength steel: Annealed:				
	40	"Advanced" or "ultra" of a kind described				
	10	in statistical note 4 to this chapter				
	45	•	, and			
	60	OtherOther				
	00	Other:	Ny			
	70	Annealed	kg			
			ľ			
	91	Other	kg			
					Ī	

	Stat. Suf-	Article Description	Unit of		Rates of Duty	2
Subileading	fix	Atticle Description	Quantity	General	Special	
7209 (con.)		Flat-rolled products of iron or nonalloy steel, of a width of 600 mm or more, cold-rolled (cold-reduced), not clad, plated or coated: (con.) In coils, not further worked than cold-rolled (cold-reduced): (con.)				
7209.17.00		Of a thickness of 0.5 mm or more but not exceeding 1 mm		Free ^{3/}		0.4¢/kg + 20%
	40	Of high-strength steel: Annealed:				
	40	"Advanced" or "ultra" of a kind described in statistical note 4 to this chapter	kg			
	45 60	Other Other:				
	70 91	Annealed Other	Ŭ			
7209.18 7209.18.15	31	Of a thickness of less than 0.5 mm: Of high-strength steel		Free ^{3/}		0.4¢/kg + 20%
	30 60	AnnealedOther	J			
7209.18.25		Other: Of a thickness of less than 0.361 mm				
	20	(blackplate)Annealed	kg	Free ³		20%
7209.18.60	85	OtherOther		Free ^{3/}		0.4¢/kg + 20%
	20 90	Annealed Other Not in coils, not further worked than cold-rolled (cold-reduced):	ľ			
7209.25.00	00	Of a thickness of 3 mm or more	kg	Free ^{3/}		0.4¢/kg + 20%
7209.26.00		Of a thickness exceeding 1 mm but less than 3 mm	kg	Free ^{3/}		0.4¢/kg + 20%
7209.27.00	00	Of a thickness of 0.5 mm or more but not exceeding 1 mm				0.4¢/kg + 20%
7209.28.00 7209.90.00		Of a thickness of less than 0.5 mm Other				0.4¢/kg + 20° 0.4¢/kg + 20°
			J			

	Х	V
72	-1	7

	Stat.	Auticle Description	Unit		Rates of Duty	
Subheading	Suf- fix	Article Description	of Quantity	General	1 Special	2
210		Flat-rolled products of iron or nonalloy steel, of a width of 600 mm or more, clad, plated or coated:				
210.11.00	00	Plated or coated with tin: Of a thickness of 0.5 mm or more	kg	Free ^{3/}		6%
210.12.00	00	Of a thickness of less than 0.5 mm	ka	Free ^{3/}		6%
210.20.00		Plated or coated with lead, including terne-plate	-			6%
7210.30.00		Electrolytically plated or coated with zinc				21.5%
	30	Of high-strength steel		1100		
	60	Other	kg			
7040 44 00		Otherwise plated or coated with zinc:		01		0.4 504
7210.41.00	00	Corrugated				21.5%
7210.49.00		Other		Free ^{3/}		21.5%
	40	Of high-strength steel: "Advanced" or "ultra" of a kind described in	l.a.			
	4.5	statistical note 4 to this chapter	•			
	45	Other:Other:	kg			
	91	Of a thickness of 0.4 mm or more	kg			
	95	Other				
7210.50.00		Plated or coated with chromium oxides or with chromium		_ 3/		45%
	20	and chromium oxides Of a width less than 1050 mm		Free		45%
	90	Other	J			
	90	Plated or coated with aluminum:	ĸg			
7210.61.00	00	Plated or coated with aluminum-zinc alloys	kg	Free ^{3/}		21.5%
7210.69.00	00	Other	kg	Free ^{3/}		21.5%
7210.70	00	Painted, varnished or coated with plastics:	l. a.	_ 3/		0.4+// 000
7210.70.30	00	Not coated or plated with metal and not clad	_			0.4¢/kg + 20°
7210.70.60		Other		Free ^{3/}		21.5%
	30	Zinc coated or plated: Electrolytically coated or plated	kg			
	60	Other	kg			
	90	Other	kg			
7210.90 7210.90.10	00	Other: Clad	ka	F ₂₀₀ 3/		30%
7 2 10.50.10	00		ку	Free-		00 /0
7210.90.60	00	Other: Electrolytically coated or plated with base metal	kg	Free ^{3/}		45%
7210.90.90		Other	_			21.5%
210.50.50	00	Othor	ку	Free-		21.576
						1

	Stat. Suf-	Article Description	Unit of	 	Rates of Duty 1	2
	fix	·	Quantity	General	Special	
'211		Flat-rolled products of iron or nonalloy steel, of a width of less than 600 mm, not clad, plated or coated:				
7211.13.00	00	Not further worked than hot-rolled: Universal mill plate	kg	· Free ^{3/}		20%
211.14.00		Other, of a thickness of 4.75 mm or more				20%
	30	Of high-strength steel		1166		
		Other:				
	45	Not in coils	•			
'211.19	90	OtherOther:	kg			
		Of a width of less than 300 mm:				
7211.19.15	00	Of high-strength steel	kg	Free ^{3/}		25%
7044 40 00	00	Other:	l .	3/		050/
7211.19.20		Of a thickness exceeding 1.25 mm				25%
7211.19.30	00	OtherOther:	kg	Free ^{3/}		25%
7211.19.45	00	Of high-strength steel	kg	· Free ^{3/}		20%
		Other:				
7211.19.60	00	Pickled	kg	Free ^{3/}		0.4¢/kg + 20°
211.19.75		Other		Free ^{3/}		20%
	00	In coils:	t			
	30	With untrimmed edges	•			
	60 90	Other				
			9			

Х	١
72-1	C

Subheading	Stat.	A C L D	Unit		Rates of Duty	
Subfleading	Suf- fix	Article Description	of Quantity	General	1 Special	2
211 (con.)		Flat-rolled products of iron or nonalloy steel, of a width of less		General	Ореска	
(/		than 600 mm, not clad, plated or coated: (con.)				
		Not further worked than cold-rolled (cold-reduced):				
211.23		Containing by weight less than 0.25 percent of carbon:				
		Of a width of less than 300 mm: Of a thickness exceeding 1.25 mm:				
211.23.15	00	Of high-strength steel	kg	. Free ^{3/}		25%
211.23.20	00	Other				25%
211.23.20			ку	· Free ^{ss}		25%
211.23.30	00	Of a thickness exceeding 0.25 mm but not exceeding 1.25 mm	ka	Eroo <u>3/</u>		25%
2011 00 15						
211.23.45	00	Of a thickness not exceeding 0.25 mm				25%
211.23.60	20	Other		Free ^s		0.4¢/kg + 20%
	30	Of a thickness exceeding 1.25 mm	кд			
	60	Of a thickness exceeding 0.25 mm but not	l. a.			
		exceeding 1.25 mm	ŭ			
	90	Of a thickness not exceeding 0.25 mm:	kg			
'211.29		Other: Of a width of less than 300 mm:				
211.29.20		Of a thickness exceeding 0.25 mm		Eroo <u>3/</u>		25%
	30	Of a width less than 51 mm, in coils		1166		
	90	Other	_			
	00	Other		Eroo <u>3/</u>		25%
211.29.60	•	Other				0.4¢/kg + 20%
	30	Of a thickness exceeding 1.25 mm		1166		σ. τφ/πg + 2σ /
	80	Other	_			
	00	Other		Eroo <u>3/</u>		20%
211.00.00	•	Flat-rolled products of iron or nonalloy steel, of a width of less		Triee		20 70
		than 600 mm, clad, plated or coated:				
7212.10.00	00	Plated or coated with tin	kg	· Free ^{3/}		6%
212.20.00	00	Electrolytically plated or coated with zinc	ka	Eroo <u>3/</u>		21.5%
				Triee		21.676
'212.30		Otherwise plated or coated with zinc: Of a width of less than 300 mm:				
212.30.10		Of a thickness exceeding 0.25 mm or more		Free ^{3/}		25%
	30	Of a width less than 51 mm, in coils				
	90	Other	kg			
	00	Other		Froo ^{3/}		25%
7212.30.50	00	Other				21.5%
7212.40		Painted, varnished or coated with plastics:				
7212.40.10	00	Of a width of less than 300 mm	kg	· Free ^{3/}		25%
7212.40.50	00	Other				0.4¢/kg + 20%
7212.50.00		Otherwise plated or coated				21.5%
212.60.00	00	Clad	kg	· Free ^{3/}		30%
				1	1	1

Heading/ Subheading	Stat. Suf-	Article Description	Unit of		Rates of Duty 1	2
	fix	·	Quantity	General	Special	
213		Bars and rods, hot-rolled, in irregularly wound coils, of iron or nonalloy steel:				
213.10.00	00	Concrete reinforcing bars and rods	kg	Free ^{3/}		20%
213.20.00		Other, of free-cutting steel		Free ^{3/}		5.5%
	10	Containing by weight 0.1 percent or more of lead				
	80	Other:Other:	kg			
213.91		Of circular cross section measuring less than 14 mm				
213.91.30		in diameter: Not tempered, not treated and not partly manufactured		Free ^{3/}		5.5%
	11	Tire cord-quality steel wire rod as defined in statistical note 4 of this chapter		1100		
	15	Of Cold Heading Quality (CHQ) steel, as defined in statistical note 5 to this chapter	kg			
	20	Of welding quality wire rods as defined in statistical note 6 to this chapter	kg			
	93	Other	kg			
213.91.45	00	Other: Containing by weight 0.6 percent or more of carbon	ka	Eroo <u>^{3/}</u>		5.5%
213.91.60	00	Other				6%
213.91.00	00	Other				5.5%
		Of circular cross section:				
	30	With a diameter of 14 mm or more but less than 19 mm	ka			
	60	With a diameter of 19 mm or more	Ŭ			
	90	Other				
						1

	>	(V
72	_′	2	1

	Stat.	Artiala Description	Unit		Rates of Duty	1 0
Subheading	Suf- fix	Article Description	of Quantity	General	1 Special	2
214		Other bars and rods of iron or nonalloy steel, not further worked than forged, hot-rolled, hot-drawn or hot-extruded, but including			·	
214.10.00	00	those twisted after rolling: Forged		Free ^{4/}		20%
214.20.00		Concrete reinforcing bars and rods				20%
214.30.00		Other, of free-cutting steel		Free ^{3/}		20%
	10 80	Containing by weight 0.1 percent or more of lead				
	00	Other:	J			
7214.91.00		Of rectangular (other than square) cross-section Containing by weight less than 0.25 percent of carbon:		Free ³ /		20%
	16	With a maximum cross section less than 152 mm	kg			
	20	With a maximum cross section of 152 mm or	J			
	60	more Containing by weight 0.25 percent or more but less than 0.6 percent of carbon	_			
	90	Containing by weight 0.6 percent or more of carbon				
7214.99.00		Other		Free ^{3/}		20%
		Rounds: Containing by weight less than 0.25 percent of carbon:				
	16	With a diameter less than 76 mm	Ŭ			
	21	With a diameter of 76 mm or more but not exceeding 152 mm	kg			
	26 31	With a diameter exceeding 152 mm Containing by weight 0.25 percent or more but less than 0.6 percent of carbon: With a diameter less than 76 mm				
	36	With a diameter less than 70 mm With a diameter of 76 mm or more but not exceeding 152 mm				
	40	With a diameter exceeding 152 mm	_			
	45	Containing by weight 0.6 percent or more of carbon	kg			
	60	Containing by weight less than 0.25 percent of carbon	kg			
	75	Containing by weight 0.25 percent or more but less than 0.6 percent of carbon				
	90	Containing by weight 0.6 percent or more of				
		carbon	кд			

	Stat. Suf-	Article Description	Unit of		Rates of Duty	2
Jubilicaulily	fix	<u> </u>	Quantity	General	Special	
215 215.10.00		Other bars and rods of iron or nonalloy steel: Of free-cutting steel, not further worked than cold-formed or cold-finished		Eroo <u>^{3/}</u>		0.3¢/kg + 20°
	10	Containing by weight 0.1 percent or more of lead	kg	1166		0.5¢/πg γ 25
7215.50.00	80	OtherOther, not further worked than cold-formed or cold-finished		Free ^{3/}		0.3¢/kg + 20°
	16	Containing by weight less than 0.25 percent of carbon: With a diameter or cross section measuring less than 76 mm		11166		July in grand
	18	With a diameter or cross section measuring 76 mm or more but not exceeding 228 mm				
	20	With a diameter or cross section exceeding 228				
		mm Containing by weight 0.25 percent or more but less than 0.6 percent of carbon:	kg			
	61	With a diameter or cross section measuring less than 76 mm	kg			
	63	With a diameter or cross section measuring 76 mm or more but not exceeding 228 mm	kg			
	65	With a diameter or cross section exceeding 228 mm	kg			
215.90	90	Containing by weight 0.6 percent or more of carbon Other:	kg			
215.90.10	00	Plated or coated with metal: Not cold-formed	kg	Free ^{3/}		0.4¢/kg + 20
215.90.30 215.90.50		Cold-formedOther				0.3¢/kg + 20 0.3¢/kg + 20

	>	(١
72	٠	2	•

	Stat.	A 2 L D	Unit		Rates of Duty	_
Subheading	Suf- fix	Article Description	of Quantity	General	1 Special	2
216		Angles, shapes and sections of iron or nonalloy steel:	,	Conorai	Оросіа:	
216.10.00		U, I or H sections, not further worked than hot-rolled,				
		hot-drawn or extruded, of a height of less than 80 mm		Free ^{3/}		2%
	10	U sections	kg			
	50	Other	ka			
		L or T sections, not further worked than hot-rolled,	J			
		hot-drawn or extruded, of a height of less than 80 mm:				
216.21.00	00	L sections	kg	Free ^{3/}		2%
216.22.00	00	T sections	ka	Froo ^{3/}		2%
		U, I or H sections, not further worked than hot-rolled,		1166		
		hot-drawn or extruded, of a height of 80 mm or more:				
216.31.00	00	U sections	kg	Free ^{3/}		2%
216.32.00	00	I sections (standard beams)	ka	F 3/		2%
	00		_			
216.33.00		H sections		Free ^{3/}		2%
	30	Weighing not more than 11.3 kg per 30.5 cm, with				
		a web depth measuring 102 mm to 356 mm	kg			
	60	Weighing more than 11.3 kg but not more than				
		27.2 kg per 30.5 cm, with a web depth measuring				
		203 mm to 457 mm	kg			
	90	Other	kg			
216.40.00		L or T sections, not further worked than hot-rolled,				
		hot-drawn or extruded, of a height of 80 mm or more		Free ^{3/}		2%
	10	L sections	kg			
	50	Other	kg			
216.50.00	00	Other angles, shapes and sections, not further worked				
		than hot-rolled, hot-drawn or extruded	kg	Free ^{3/}		2%
		Angles, shapes and sections, not further worked than				
		cold-formed or cold-finished:				
216.61.00	00	Obtained from flat-rolled products	kg	Free ^{1/}		20%
216.69.00	00	Other				20%
210.09.00	00	Other:	kg	Free=		20%
216.91.00		Cold-formed or cold-finished from flat-rolled				
210.01.00		products		Froo ^{1/}		20%
	10	Drilled, notched, punched or cambered		1166		
	90					
216.99.00	90	Other	kg	- 3/		20%
	10	Drilled, notched, punched or cambered		Free ^{3/}		20%
		•	ку			
	90	Other	kg			
				Ī		Ī

Suf- fix	Article Description	Quantity	General	Cassial	
		Quantity	Gericiai	Special	
	Wire of iron or nonalloy steel: Not plated or coated, whether or not polished:				
	Containing by weight less than 0.25 percent of carbon: Flat wire:				
00	Of a thickness not exceeding 0.25 mm	kg	Free ^{3/}		25%
00	Of a thickness exceeding 0.25 mm but not exceeding 1.25 mm	kg	Free ^{3/}		25%
00	_	kg	Free ^{3/}		25%
	Round wire: With a diameter of less than 1.5 mm		Free ^{3/}		25%
40	Heat treated: In coils weighing not more than 2 kilograms	ka			
45	_	•			
90	Other	kg			
	With a diameter of 1.5 mm or more		Free ^{3/}		7%
30	Heat treated	kg			
90	Other	kg			
00		kg	Free ^{3/}		25%
00		kg	Free ^{3/}		25%
					25%
			Free		2570
10	Heat treated	kg			
20	Other Containing by weight 0.6 percent or more of carbon:	kg			
25	Heat treated: With a diameter of less than 1.0 mm	ka			
30	With a diameter of 1.0 mm or more but	J			
45	With a diameter of 1.5 mm or more	kg			
60	With a diameter of less than 1.0	ka			
75	With a diameter of 1.0 mm or more but	J			
90		Ü			
00			Free ^{3/}		25%
	40 45 90 30 90 00 00 10 20 25 30 45 60 75 90	Of a thickness exceeding 1.25 mm	00 Of a thickness exceeding 1.25 mm	00 Of a thickness exceeding 1.25 mm	Of a thickness exceeding 1.25 mm

	X	١
72	2	ı

	Stat.	A C L D	Unit		Rates of Duty	
ubheading	Suf- fix	Article Description	of Quantity	General	1 Special	2
217 (con.)		Wire of iron or nonalloy steel: (con.)	ĺ			
217.20		Plated or coated with zinc:				
217.20.15	00	Flat wire	kg	Free ^{3/}		26%
		Round wire:				
217.20.30	00	With a diameter of 1.5 mm or more and containing				
		by weight less than 0.25 percent of carbon 5	kg	Free ^{3/}		7%
217.20.45		Other		Froo ^{3/}		25%
217.20.40		With a diameter of less than 1.0 mm:		Free-		2576
	10	Containing by weight less than 0.25				
		percent of carbon	kg			
	20	Containing by weight 0.25 percent or more				
		but less than 0.6 percent of carbon				
	30	Containing by weight 0.6 percent or more	_			
	00	of carbon ^{6/}				
		With a diameter of 1.0 mm or more but less	Ng			
		than 1.5 mm:				
	40	Containing by weight less than 0.25				
		percent of carbon	kg			
	50	Containing by weight 0.25 percent or more				
		but less than 0.6 percent of carbon	kg			
	60	Containing by weight 0.6 percent or more				
		of carbon	kg			
	70	With a diameter of 1.5 mm or more:				
	70	Containing by weight 0.25 percent or more but less than 0.6 percent of carbon				
			•			
	80	Containing by weight 0.6 percent or more				
		of carbon Other:	кд			
217.20.60	00	Containing by weight less than 0.25 percent of				
		carbon	kg	Free ^{3/}		25%
217.20.75	00					26%
217.20.75	00	Other	ку	Free=		20%
					1	
					1	
					1	
					1	
					1	
					1	
				Ī	1	

Value Containing by weight less than 0.25 percent or more but less than 0.6 percent or more of carbon	Heading/ Subheading	Stat. Suf-	Article Description	Unit of	-	Rates of Duty 1	2
Plated or coated with other base metals: Flat wire	oublieadilig		Atticle Description		General	-	
30 Containing by weight 0.6 percent or more of carbon	217.30		Plated or coated with other base metals:		Free ^{3/}		26%
Round wire: With a diameter of 1.5 mm or more and containing by weight less than 0.25 percent of carbon		30	Containing by weight 0.6 percent or more of		1100		
Other	217.30.30		Round wire:				
Other: With a diameter of less than 0.20 percent or welding	247.00.45						
With a diameter of less than 1.0 mm: Containing by weight less than 0.25 percent of carbon	217.30.45	04	Containing by weight less than 0.20 percent of carbon, and suitable for electric arc		Free		25%
20		11	With a diameter of less than 1.0 mm: Containing by weight less than 0.25	ka			
Mith a diameter of 1.0 mm or more but less than 0.25 percent or more but less than 1.5 mm: Containing by weight less than 0.25 percent or more but less than 0.6 percent or more but less than 0.6 percent or more of carbon		20	Containing by weight 0.25 percent or more but less than 0.6 percent or				
41 Containing by weight less than 0.25		30	more of carbonWith a diameter of 1.0 mm or more but less				
50 Containing by weight 0.25 percent or more but less than 0.6 percent or more but less than 0.6 percent or more of carbon		41	Containing by weight less than 0.25	kg			
More of carbon		50	Containing by weight 0.25 percent or more but less than 0.6 percent of				
217.30.60 Other: Containing by weight less than 0.25 percent of carbon		60	Containing by weight 0.6 percent or more of carbon	kg			
Carbon			Other:	kg			
217.90 Other: Coated with plastics	217.30.60	00	Containing by weight less than 0.25 percent of carbon	kg	· Free ^{3/}		25%
217.90.10 00 Coated with plastics		00		kg	· Free ^{3/}		26%
Containing by weight less than 0.25 percent of carbon	217.90.10	00	Coated with plastics				
Containing by weight 0.25 percent or more but less than 0.6 percent of carbonkg Containing by weight 0.6 percent or more of	217.90.50	30	Containing by weight less than 0.25 percent of		Free ^{3/}		35%
		60	Containing by weight 0.25 percent or more but less				
		90		kg			

	X١
72	-2.

Heading/ Subheading	Stat.	Article Description	Unit			
Subheading	Suf- fix	Article Description	of Quantity	General	1 Special	2
		III. STAINLESS STEEL				
218		Stainless steel in ingots or other primary forms; semi-finished				
218.10.00	00	products of stainless steel: Ingots and other primary forms	kg	Free ^{3/}		29%
2040 04 00		Other:		2/		000/
'218.91.00		Of rectangular (other than square) cross-section Having a width less than four times the thickness:		Free ³		29%
	15	Having a cross-sectional area of less than 232 cm²	kg			
	30	Having a cross-sectional area of 232 cm ² or				
	60	more Having a width at least four times the thickness	kg			
218.99.00		Other Of square cross section:		Free ^{3/}		29%
	15	Having a cross-sectional area of less than 232 cm ²	ka			
	30	Having a cross-sectional area of 232 cm ² or				
		more Of circular cross section:	kg			
	45	Having a cross-sectional area of less than 232 cm ²	ka			
	60	Having a cross-sectional area of 232 cm ² or				
	90	more Other	-			
'219		Flat-rolled products of stainless steel, of a width of 600 mm or more:				
219.11.00		Not further worked than hot-rolled, in coils: Of a thickness exceeding 10 mm		Free ^{3/}		29%
	30	Of a width not exceeding 1575 mm				
	60	Of a width exceeding 1575 mm	kg			

	Stat. Suf-	Article Description	Unit of		Rates of Duty	2
Subheading	fix	Article Description	or Quantity	General	1 Special	┥ ′
219 (con.)		Flat-rolled products of stainless steel, of a width of 600 mm or		5 5 1 1 5 1 5 1		
,		more: (con.)				
		Not further worked than hot-rolled, in coils: (con.)				
219.12.00		Of a thickness of 4.75 mm or more but not exceeding				
		10 mm		Free ^{3/}		29%
	02	Not annealed or not pickled	kg			
		Other:				
	06	Of high-nickel alloy steel	ka			
		Other:	9			
		Of a width of 1370 mm or more:				
		Of a thickness exceeding 6.8 mm:				
	21	Of a width not exceeding				
		1575 mm	ka			
	26		•			
	26	Of a width exceeding 1575 mm Other:	kg			
	51	Officer. Of a width not exceeding				
	51	1575 mm	ka			
			•			
	56	Of a width exceeding 1575 mm	kg			
		Other:				
		Containing more than 0.5 percent by weight of nickel:		1		
	66	Weight of flicker. Containing more than 1.5 percent				
	00	but less than 5 percent by weight				
		of molybdenum				
	74	-	ū			
	71 81	Other				
219.13.00	01	Other Of a thickness of 3 mm or more but less than	kg			
219.13.00		4.75 mm		- 3/		29%
	02			Free ^{3/}		29 /6
	02	Not annealed or not pickled	kg			
		Other:				
	31	Of a width of 1370 mm or more	kg			
		Other:				
		Containing more than 0.5 percent but less				
		than 24 percent by weight of nickel:				
	51	Containing more than 1.5 percent but				
		less than 5 percent by weight of				
		molybdenum	kg			
	71		kg			
	81	Other				
219.14.00		Of a thickness of less than 3 mm		Free ^{3/}		29%
	30	Of a width of 1370 mm or more	kg	1		
		Other:				
	65	Of high-nickel alloy steel	kg	1		
			_	1		
	90	Other	ky	1		
				1		
				1		
				1		
				1		
				1		
				1		
				1		
				1		
				1		
				1		
	ı			1		1

	>	(١
72	٠	2	(

	Stat.	Article Description	Unit		Rates of Duty	2
Subheading	Suf- fix	Article Description	of Quantity	General	1 Special	2
219 (con.)		Flat-rolled products of stainless steel, of a width of 600 mm or				
		more: (con.) Not further worked than hot-rolled, not in coils:				
219.21.00		Of a thickness exceeding 10 mm		Free ^{3/}		29%
	05	Of high-nickel alloy steel				
		Other:				
	20	Of a width not exceeding 1575 mm	kg			
	40	Of a width exceeding 1575 mm but not	l.a.			
	00	exceeding 1880 mm	_			
7219.22.00	60	Of a width exceeding 1880 mm Of a thickness of 4.75 mm or more but not exceeding				
		10 mm		Free ^{3/}		29%
	05	Of high-nickel alloy steel	kg			
		Other:				
		Containing more than 0.5 percent by weight of nickel:				
		Containing more than 1.5 percent but less				
	4.5	than 5 percent by weight of molybdenum:	Lan			
	15	Of a width not exceeding 1575 mm	•			
	20	Of a width exceeding 1575 mm but not exceeding 1880 mm				
	25	Of a width exceeding 1880 mm	_			
		Other:				
	35	Of a width not exceeding 1575 mm	_			
	40	Of a width exceeding 1575 mm but not				
	45	exceeding 1880 mm				
	45	Of a width exceeding 1880 mm Other:	kg			
	70	Of a width not exceeding 1575 mm	kg			
	75	Of a width exceeding 1575 mm but not				
		exceeding 1880 mm	_			
7219.23.00	80	Of a width exceeding 1880 mm Of a thickness of 3 mm or more but less than	kg			
210.20.00		4.75 mm		Free ^{3/}		29%
	30	Of a width of 1370 mm or more	kg			
	60	Other	J			
7219.24.00	30	Of a thickness of less than 3 mm Of a width of 1370 mm or more		Free ^{3/}		29%
			J			
	60	Other	kg			
			I	ī		•

	Stat. Suf-	Article Description	Unit of	-	Rates of Duty 1	2
_	fix		Quantity	General	Special	<u> </u>
219 (con.)		Flat-rolled products of stainless steel, of a width of 600 mm or				
		more: (con.) Not further worked than cold-rolled (cold-reduced):				
219.31.00		Of a thickness of 4.75 mm or more		Frac ^{3/}		29%
210.01.00	10	In coils		riee-		2370
	50		•			
'219.32.00	50	Not in coilsOf a thickness of 3 mm or more but less than	· ·	F3/		29%
		In coils:		riee		25 /0
	05	Of a width of 1370 mm or more: Of high-nickel alloy steel	ka			
	20	Other: Containing more than 0.5 percent by	9			
	20	weight of nickel	ka			
	O.E.					
	25	Other:Other:	kg			
	35	Of high-nickel alloy steel	kg			
		Other: Containing more than 0.5 percent by				
		weight of nickel:				
	36	Containing more than 1.5 percent				
		but less than 5 percent by weight	Lan			
		of molybdenum	J			
	38	Other:Other:	kg			
	42	Containing less than 15 percent by weight of chromium	kg			
	44	Other	kg			
	45	Not in coils: Of a width of 1370 mm or more	l. a			
	_		•			
	60	Other	kg			
						1

)	<	١
72	_	3	•

Heading/	Stat.	Auticle Description	Unit		Rates of Duty	
Subheading	Suf- fix	Article Description	of Quantity	General	1 Special	2
219 (con.)		Flat-rolled products of stainless steel, of a width of 600 mm or	,			
		more: (con.)				
		Not further worked than cold-rolled (cold-reduced): (con.)				
219.33.00				Free ^{3/}		29%
		In coils:				
	٥.	Of a width of 1370 mm or more:				
	05	Of high-nickel alloy steel	kg			
		Other:				
	20	Containing more than 0.5 percent by				
		weight of nickel	kg			
	25	Other	kg			
		Other:				
	35	Of high-nickel alloy steel	kg			
		Other:				
		Containing more than 0.5 percent by				
		weight of nickel:				
	36	Containing more than 1.5 percent				
		but less than 5 percent by weight				
		of molybdenum	kg			
	38	Other	kg			
		Other:				
	42	Containing less than 15 percent				
		by weight of chromium	kg			
	44	Other	kg			
		Not in coils:	3			
	45	Of a width of 1370 mm or more	kg			
		Other:				
	70	Containing more than 0.5 percent but less				
		than 24 percent by weight of nickel				
	80	Other	ka			
219.34.00	00	Of a thickness of 0.5 mm or more but not exceeding	Ng			
				Free ^{3/}		29%
		In coils:		1100		
	05	Of high-nickel alloy steel	kg			
		Other:	3			
		Containing more than 0.5 percent by				
		weight of nickel:				
	20	Containing more than 1.5 percent but				
		less than 5 percent by weight of				
		molybdenum	kg			
	25	Other	kg			
		Other:	3			
	30	Containing less than 15 percent by				
		weight of chromium	kg			
	35	Other	kg			
	50	Not in coils				
	l			Ī	1	Ī

Subheading	Suf-	Article Description	Unit of		Rates of Duty 1	2
_	fix	·	Quantity	General	Special	
219 (con.)		Flat-rolled products of stainless steel, of a width of 600 mm or				
7219.90.00		more: (con.) Not further worked than cold-rolled (cold-reduced): (con.)				
		Of a thickness of less than 0.5 mm		Eroo ^{3/}		29%
		In coils:		1166		12070
		Containing more than 0.5 percent but less than				
		24 percent by weight of nickel:				
	05	Containing more than 1.5 percent but less				
		than 5 percent by weight of molybdenum	ka			
	. –	-	•			
	15	OtherOther:	kg			
	30	Containing less than 15 percent by weight				
	00	of chromium	kg			
	35	Other	•	Free ^{3/}		
	50	Not in coils				
		Other				29%
	10	Of high-nickel alloy steel				
		Other:				
		Containing more than 0.5 percent by weight of				
		nickel:				
	20	Containing more than 1.5 percent but less than				
		5 percent by weight of molybdenum	_			
	25	Other	kg			
	60	Other: Containing less than 15 percent by weight of				
	JU	chromium	ka			
	80	Other	•			
	80	Otrier	kg			
						1

)	<	١
72	_	3	•

Heading/	Stat.		Unit Rates of Duty				
Subheading	Suf- fix	Article Description	of Quantity	General	1 Special	2	
220		Flat-rolled products of stainless steel, of a width of less than	,	- Constan	Opera		
		600 mm:					
000 11 00	00	Not further worked than hot-rolled:	l.	2/		000/	
220.11.00	00	Of a thickness of 4.75 mm or more	kg	Free ³		29%	
220.12		Of a thickness of less than 4.75 mm:					
220.12.10	00	Of a width of 300 mm or more	kg	· Free ^{3/}		29%	
220.12.50	00	Of a width of less than 300 mm	kg	Free ^{3/}		34%	
				1			
				1			
				1			
				1			
				1			
				1			
				1			
				1			
				1			
				1			
				1			
				•			

	Stat. Suf-	Article Description	Unit of		Rates of Duty 1	2
Jubileaulig	fix	Attible Description	Quantity	General	Special	
220 (con.)		Flat-rolled products of stainless steel, of a width of less than				
		600 mm: (con.)				
220.20 220.20.10		Not further worked than cold-rolled (cold-reduced): Of a width of 300 mm or more		– 3/		29%
220.20.10		Containing more than 0.5 percent but less than 24		Free		29%
		percent by weight of nickel:				
	10	Containing more than 1.5 percent but less than				
		5 percent by weight of molybdenum				
	15	Other	kg			
		Other:	3			
	60	Containing less than 15 percent by weight of				
		chromium	kg			
	80	Other	kg			
200 00 00		Of a width of less than 300 mm:		2/		0.40/
220.20.60	٥.	Of a thickness exceeding 1.25 mm		Free ³⁷		34%
	05	Of high-nickel alloy steel	kg			
		Other:				
		Containing more than 0.5 percent by weight of nickel:				
	10	Containing more than 1.5 percent but				
	10	less than 5 percent by weight of				
		molybdenum	kg			
	15	Other	kg			
		Other:	3			
(60	Containing less than 15 percent by				
		weight of chromium	•			
	80	Other	kg			
220.20.70		Of a thickness exceeding 0.25 mm but not		2/		0.40/
	٥.	exceeding 1.25 mm		Free ³⁷		34%
	05	Of high-nickel alloy steel	kg			
		Other:				
		Containing more than 0.5 percent by weight of nickel:				
	10	Containing more than 1.5 percent but				
		less than 5 percent by weight of				
		molybdenum	kg			
	15	Other	kg			
		Other:				
	60	Containing less than 15 percent by		1		1
		weight of chromium	•	1		1
	80	Other	kg	1		1
220.20.80	00	Of a thickness not exceeding 0.25 mm: Razor blade steel	ka	5 3/		34%
	00					
220.20.90	_	Other		Free ^{3/}		34%
	30	Containing more than 0.5 percent but less		1		1
		than 24 percent by weight of nickel		1		1
	60	Other	kg			
				1		1
				1		1
				1		1
				1		1
				1		1
				1		1
				1		1

	>	(١
72	٠	3	ı

Heading/	Stat. Suf-		Unit of		Rates of Duty	2
Subheading	fix	Article Description	Quantity	General	1 Special	
220 (con.)		Flat-rolled products of stainless steel, of a width of less than				
		600 mm: (con.)				
220.90.00		Other		Free ^{3/}		46%
		Containing more than 0.5 percent but less than 24				
	10	percent by weight of nickel: Containing more than 1.5 percent but less than 5				
	10	percent by weight of molybdenum	ka			
	15		•			
	13	Other:	kg			
	60	Containing less than 15 percent by weight of				
		chromium	kg			
	80	Other	kg			
221.00.00		Bars and rods, hot-rolled, in irregularly wound coils, of stainless				
		steel		Free ^{3/}		11%
	05	Of high-nickel alloy steel	kg			
		Other:				
		Of circular cross section:				
	47	With a diameter of less than 14 mm:				
	17	Containing less than 8 percent by weight of nickel	ka	1		
	10		•			
	18	Containing 8 percent or more but less than 24 percent by weight of nickel				
	30		ĸy			
		19 mm	kg			
	45	With a diameter of 19 mm or more	ka			
	75	Other				
			J			
				1		
				1		
				1		
				1		
				1		
				1		
				1		
				1		
				1		
				1		
				1		
				1		
	I					

	Stat. Suf-	Article Description	Unit of		Rates of Duty	2
	fix		Quantity	General	Special	<u> </u>
222		Other bars and rods of stainless steel; angles, shapes and sections of stainless steel: Bars and rods, not further worked than hot-rolled,				
222.11.00		hot-drawn or extruded: Of circular cross-section		Free ^{3/}		29%
222.11.00	01	Electroslag or vacuum arc remelted		Free-		23 /0
	06	Of high-nickel alloy steel				
	57	Other: With a maximum cross-sectional dimension of less than 152.4 mm:				
	-	Containing less than 8 percent by weight of nickel	kg			
	59	Containing 8 percent or more but less than 24 percent by weight of nickel With a maximum cross-sectional dimension of 152.4 mm or more:				
	82	Containing less than 8 percent by weight of nickel	kg			
	84	Containing 8 percent or more but less than 24 percent by weight of nickel				
'222.19.00		Other		Froo ^{3/}		29%
	01	Electroslag or vacuum arc remelted		1166		
		Other:	J			
	06	Of high-nickel alloy steel	kg			
	52	Other: Containing less than 8 percent by weight of nickel				
	E 4		_			
	54	Containing 8 percent or more but less than 24 percent by weight of nickel				
		24 percent by weight of motor	Ng			
						I

	Χ	١
72	-3	Ġ

	Stat. Suf-	Article Description	Unit of		Rates of Duty	2
Subneading	fix	Article Description	Quantity	General	Special	
'222 (con.)		Other bars and rods of stainless steel; angles, shapes and			·	
7000 00 00		sections of stainless steel: (con.)				
7222.20.00		Bars and rods, not further worked than cold-formed or cold-finished		Fran ³ /		29%
	01	Electroslag or vacuum arc remelted		Free-		23 /6
	06	Of high-nickel alloy steel	_			
	00		ĸġ			
		Other: Of a circular cross-section:				
		With a maximum circular cross-sectional				
		dimension of less than 18 mm:				
	41	Containing less than 8 percent by weight of nickel	ka			
	40		Ü			
	43	Containing 8 percent or more but less than 24 percent by weight of nickel				
		With a maximum circular cross-sectional	1.9			
		dimension of 18 mm or more and less than				
	62	152.4 mm: Containing less than 8 percent by weight				
	02	of nickel				
	64	Containing 8 percent or more but less than				
	٠.	24 percent by weight of nickel				
		With a maximum circular cross-sectional				
	67	dimension of 152.4 mm or more: Containing less than 8 percent by weight				
	07	of nickel				
	69	Containing 8 percent or more but less than	•			
	00	24 percent by weight of nickel				
		Other:				
	71	Containing less than 8 percent by weight of nickel	ka			
_	70		0			
	73	Containing 8 percent or more but less than 24 percent by weight of nickel	ka			
7222.30.00		Other bars and rods		Free ^{3/}		29%
	01	Electroslag or vacuum arc remelted				
	12	Of high-nickel alloy steel	kg			
		Other:	J			
		With a maximum cross-sectional dimension of less				
		than 152.4 mm:				
	22	Containing less than 8 percent by weight of nickel	ka			
	24	Containing 8 percent or more but less than 24	Ü			
	24	percent by weight of nickel				
		With a maximum cross-sectional dimension of	9			
	00	152.4 mm or more:				
	82	Containing less than 8 percent by weight of nickel	ka			
	84	Containing 8 percent or more but less than 24	ŭ			
	04	percent by weight of nickel				
		, , , , , , , , , , , , , , , , , , , ,	9			
				1		
				1		
				1		
				1		
				1		
				1		
				1		
						1

ading/ Staneading Su	tat. iuf-	Article Description	Unit of		Rates of Duty 1	2
	iui- fix	Atticle Description	Quantity	General	Special	
2 (con.)		Other bars and rods of stainless steel; angles, shapes and sections of stainless steel: (con.)				
2.40		Angles, shapes and sections:				
2.40.30		Hot-rolled, not drilled, not punched and not otherwise		_ 3/		100/
		advanced With a maximum cross-sectional dimension of		Free ^{3/}		10%
		80 mm or more:				
2	25	Angles	kg			
4	15	Other				
		With a maximum cross-sectional dimension of less				
6	35	than 80 mm: Angles	ka			
	35	Other	_			
-	00	Other	kg	Free ^{3/}		28%
3.00		Wire of stainless steel:				
3.00.10		Round wire		Free ^{3/}		34%
0:)5	Spring round wire	kg			
		Other:	Lan			
	16	With a diameter of less than 0.25 mm	J			
3	31	With a diameter of 0.25 mm or more but less than 0.76 mm				
1,	16	With a diameter of 0.76 mm or more but less than	· ·			
141	+0	1.52 mm				
6	31	With a diameter of 1.52 mm or more but less than	· ·			
	´	5.1 mm				
7	76	With a diameter of 5.1 mm or more	kg			
3.00.50 0	00	Flat wire	kg	Free ^{3/}		34%
3.00.90 0	00	Other	ka	Free ^{3/}		34%
				1166		0.70

	>	(١
72	٠	2	•

	Stat. Suf-	Article Description	Unit of		Rates of Duty	2
	fix	Article Description	Quantity	General	1 Special	
		IV. OTHER ALLOY STEEL; HOLLOW DRILL BARS AND RODS, OF ALLOY OR NONALLOY STEEL				
224		Other alloy steel in ingots or other primary forms; semi-finished products of other alloy steel:				
224.10.00	05	Ingots and other primary forms		Free ^{3/}		28%
	45	Other: Of tool steel	•			
224.90.00	75	OtherOther		Free ^{3/}		28%
	05	Of high-nickel alloy steel Other: Of tool steel: Of rectangular (including square) cross section:				
	15	Having a width less than four times the thickness	kg			
	25	Having a width at least four times the thickness	ka			
	35	Other: Other: Of rectangular (including square) cross section:				
	45	Having a width less than four times the thickness	kg			
	55	Having a width at least four times the thickness	kg			
	65 75	Of circular cross section Other	kg			

Heading/ Someon Subheading Someon Som		Article Description	Unit of	Rates of Duty		2	
Subfleading	Suf- fix	Article Description	Quantity	General	Special	1	
7225		Flat-rolled products of other alloy steel, of a width of 600 mm or more:					
7225.11.00	00	Of silicon electrical steel: Grain-oriented	kg	Free ^{3/}		28%	
7225.19.00	00	Other	kg	Free ^{3/}		28%	
7225.30		Other, not further worked than hot-rolled, in coils: Of a thickness of 4.75 mm or more:					
7225.30.11	10	Of tool steelOf high-speed steel		Free ^{3/}		29%	
7225.30.30	80	OtherOther	3	Free ^{3/}		28%	
	05 50	Of high-nickel alloy steel Other	_				
7225.30.51		Of a thickness of less than 4.75 mm: Of tool steel		Free ^{3/}		29%	
	10 80	Of high-speed steel Other					
7225.30.70	00	Other		Free ^{3/}		28%	
7225.40		Other, not further worked than hot-rolled, not in coils: Of a thickness of 4.75 mm or more:				000/	
7225.40.11	10	Of tool steel Of high-speed steel	kg	Free ³		29%	
7225.40.30	80	Other		Free ^{3/}		28%	
	05	Of high-nickel alloy steel	_				
7225.40.51	50	Other Of a thickness of less than 4.75 mm: Of tool steel		Eroo <u>^{3/}</u>		29%	
	10	Of high-speed steel		1166			
	30	Of ball-bearing steel	kg				
7225.40.70 7225.50	60 00	Other Other Other Other, not further worked than cold-rolled (cold-reduced):	kg	Free ^{3/}		28%	
7225.50.11	10	Of tool steel		Free ^{3/}		29%	
	30	Of ball-bearing steel	_				
	60	Other:					
7225.50.60	00	Of a thickness of 4.75 mm or more	kg	Free ^{3/}		28%	
7225.50.70	00	Of a thickness of less than 4.75 mm: Heat-resisting steel		Free ^{3/}		29%	
7225.50.80	, .	Other		Free ^{3/}		28%	
	10	Of high-nickel alloy steel	_				
	80	Other	kg				
						I	

	Χ	V
72	-4	1

Subbooding	Stat. Suf-	Article Description	Unit		Rates of Duty	2
Subheading	Sut- fix	Article Description	of Quantity	General	1 Special	2
225 (con.)		Flat-rolled products of other alloy steel, of a width of 600 mm or more: (con.)				
225.91.00	00	Other: Electrolytically plated or coated with zinc	kg	Free ^{3/}		28%
225.92.00	00	Otherwise plated or coated with zinc	kg	Free ^{3/}		28%
225.99.00	40	Other		Free ^{3/}		28%
	10 90	Of high-nickel alloy steel Other	•			
226	90	Flat-rolled products of other alloy steel, of a width of less than 600 mm:				
226.11 226.11.10	00	Of silicon electrical steel: Grain-oriented: Of a width of 300 mm or more	le a	- 3/		28%
226.11.10	00	Of a width of less than 300 mm				33%
220.11.90	30	Of a width of less than 300 mm		Free=		33%
	60	Other	kg			
226.19 226.19.10	00	Other: Of a width of 300 mm or more	kg	Free ^{3/}		28%
226.19.90	00	Of a width of less than 300 mm				33%
226.20.00	00	Of high-speed steel				37%
			1			

	Stat. Suf-	Article Description	Unit of	-	Rates of Duty 1	2
	fix		Quantity	General	Special	<u> </u>
7226 (con.)		Flat-rolled products of other alloy steel, of a width of less than 600 mm: (con.) Other:				
7226.91		Not further worked than hot-rolled: Of tool steel (other than high-speed steel):				
7226.91.05	00	Of chipper knife steel	kg	Free ^{3/}		34%
7226.91.15		Other: Of a width of 300 mm or more		Free ^{3/}		29%
	30 60	Of ball-bearing steel Other	_			
7226.91.25	30	Of a width of less than 300 mm Of ball-bearing steel		Free ^{3/}		34%
	60	Other	_			
226.91.50	00	Other: Of a thickness of 4.75 mm or more	kg	Free ^{3/}		28%
7226.91.70	00	Of a thickness of less than 4.75 mm: Of a width of 300 mm or more	kg	Free ^{3/}		28%
7226.91.80	00	Of a width of less than 300 mm	ka.	Froo ^{3/}		33%
7226.92		Not further worked than cold-rolled (cold-reduced): Of tool steel (other than high-speed steel):				3370
7226.92.10	30	Of a width of 300 mm or more		Free ^{3/}		0.4¢/kg + 29%
7226.92.30	60	Other Of a width of less than 300 mm		Free ^{3/}		34%
	30 60	Of ball-bearing steel Other	kg	1100		
7226.92.50		Other: Of a width of 300 mm or more		Free ^{3/}		0.4¢/kg + 28%
		Of a width of less than 300 mm:				
7226.92.70	05	Of a thickness not exceeding 0.25 mm Of high-nickel alloy steel	kg	Free ³⁴		33%
7226.92.80	50	OtherOf a thickness exceeding 0.25 mm		Free ^{3/}		33%
	05 50	Of high-nickel alloy steel Other	kg kg			
7226.99.01	10	Other Electrolytically plated or coated with zinc		Free ^{3/}		33%
	30	Otherwise plated or coated with zinc				
	80	Other	_			

	Χ	V
72	-4	3

	Stat.	Auticle Description	Unit		Rates of Duty	
Subheading	Suf- fix	Article Description	of Quantity	General	1 Special	2
227		Bars and rods, hot-rolled, in irregularly wound coils, of other alloy steel:				
227.10.00	00	Of high-speed steel	kg	Free ^{3/}		14%
227.20.00		Of silico-manganese steel		Free ^{3/}		10%
	30	Of welding quality wire rods as defined in statistical				
		note 6 to this chapter	_			
207.00	80	Other	kg			
227.90		Other: Of tool steel (other than high-speed steel):				
227.90.10		Not tempered, not treated, and not partly manufactured		Free ^{3/}		12%
	30	Of ball-bearing steel		riee		1270
	60	Other	-			
227.90.20		Other	•	Free ^{3/}		11%
	30	Of ball-bearing steel				
	60	Other	kg			
227.90.60		Other		Free ^{3/}		10%
	05	Of high-nickel alloy steel	kg			
	10	Of Cold Heading Quality (CHQ) steel, as defined in statistical note 5 to this chapter				
	20	Of welding quality wire rods as defined in statistical note 6 to this chapter				
	30	Of a circular cross section: With a diameter of less than 14 mm				
			ĸġ			
	35	With a diameter of 14 mm or more but less than 19 mm	kg			
	40	With a diameter of 19 mm or more	•			
	90	Other	0			
					1	I

10 30 60	Article Description Other bars and rods of other alloy steel; angles, shapes and sections, of other alloy steel; hollow drill bars and rods, of alloy or nonalloy steel: Bars and rods, of high-speed steel		General	1 Special	2
30	sections, of other alloy steel; hollow drill bars and rods, of alloy or nonalloy steel: Bars and rods, of high-speed steel				
30					
			Free ^{3/}		32%
60	Cold-formed: With a maximum cross-sectional dimension of less than 18 mm	3			
	With a maximum cross-sectional dimension of 18 mm or more				
00	Bars and rods, of silico-manganese steel: Not cold-formed		Free ^{3/}		28%
00	Cold-formed				28%
	Other bars and rods, not further worked than hot-rolled, hot-drawn or extruded: Of tool steel (other than high-speed steel):				
00					29%
00					28%
00					29% 28%
05					
10	Concrete reinforcing bars and rods	kg			
15	Other: With a diameter or cross section measuring less than 76 mm	kg			
41	With a diameter or cross section measuring 76 mm or more but not exceeding 152 mm	kg			
45	With a diameter or cross section measuring 152 mm or more but not exceeding 228 mm	kg			
70	With a diameter or cross section exceeding	ka			
00			Free ^{3/}		28%
	00 00 05 10 15 41 45	Of ball-bearing steel	Of ball-bearing steel	Of ball-bearing steel	Of ball-bearing steel

X	١
72-4	c

Heading/	Stat.	Auticle Description	Unit	Rates of Duty			2
Subheading	Suf- fix	Article Description	of Quantity	General	1	Special	_ 2
7228 (con.)		Other bars and rods of other alloy steel; angles, shapes and				•	
		sections, of other alloy steel; hollow drill bars and rods, of alloy					
7000 E0		or nonalloy steel: (con.)					
'228.50		Other bars and rods, not further worked than cold-formed or cold-finished:					
228.50.10		Of tool steel (other than high-speed steel)		Free ^{3/}			29%
	10	Of ball-bearing steel		1100			
		Other:					
		With a maximum cross-sectional dimension of					
		less than 18 mm:					
	20	Of round or rectangular cross section with					
		surfaces ground, milled or polished	_				
	40	Other	kg				
		With a maximum cross-sectional dimension of 18 mm or more:					
	60	Of round or rectangular cross section with					
		surfaces ground, milled or polished					
	80	Other	ka				
228.50.50		Other		Free ^{3/}			28%
	05	Of high-nickel alloy steel					
		Other:					
	15	With a diameter or cross section measuring					
		less than 76 mm	kg				
	40	With a diameter or cross section measuring					
		76 mm or more but not exceeding 228 mm	kg				
	70	With a diameter or cross section exceeding					
		228 mm	kg				
7228.60		Other bars and rods:					
7228.60.10		Of tool steel (other than high-speed steel)		Free ^{3/}			29%
	30	Of ball-bearing steel	_				
	60	Other	kg				
7228.60.60	00	Other: Not cold-formed	l. a	_ 3/			200/
220.00.00	00		_				28%
7228.60.80	00	Cold-formed	kg	Free ^{3/}			28%
7228.70		Angles, shapes and sections:					
7228.70.30		Hot-rolled, not drilled, not punched and not otherwise advanced		- 3/			10%
	10	U, I, H and T sections		Free ^{3/}			10 /8
	10		Ng				
		Other: With a maximum cross-sectional dimension of					
		76 mm or more:					
	20	Angles	kg				
	41	Other	kg				
		With a maximum cross-sectional dimension of					
		less than 76 mm:					
	60	Angles	_				
	81	Other		0/			
228.70.60	00	Other					28%
228.80.00	00	Hollow drill bars and rods	kg	Free ^{3/}			30%
	l						

Heading/ Subheading	Stat. Suf-	Article Description	Unit of		Rates of Duty	2
rubricaulity	fix	Attiole Description	Quantity	General	Special	
229		Wire of other alloy steel:				
229.20.00		Of silico-manganese steel		Free ^{3/}		33%
		Round, with a diameter of less than or equal to 1.6 mm,				
		containing by weight less than 0.20 percent of carbon,				
		more than 0.9 percent of manganese, and more than				
		0.6 percent of silicon, and suitable for electric arc welding:				
	10	Plated or coated with copper	ka			
			_			
	15 90	OtherOther				
229.90	90	Other:	ку			
229.90.05	00	Of high-speed steel	ka	Froo ^{3/}		37%
			ку	riee		07 70
200 00 40		Other:		2/		000/
229.90.10	00	Flat wire	kg	Free ³		33%
229.90.50		Round wire		Free ^{3/}		33%
		With a diameter of less than or equal to				
		1.6 mm, containing by weight less than 0.20				
		percent of carbon and more than 0.3 percent				
		of nickel or more than 0.08 percent of				
		molybdenum, and suitable for electric arc				
	06	welding: Plated or coated with copper	ka			
		• •	J			
	80	Other	kg			
	16	Other:	lea.			
	16	With a diameter of less than 1.0 mm	_			
	31	With a diameter of 1.0 mm or more but less				
		than 1.5 mm	kg			
	51	With a diameter of 1.5 mm or more	kg			
229.90.90	00	Other wire	kg	Free ^{3/}		33%
				I	I	1

Harmonized Tariff Schedule of the United States Revision 4 (2022)

Annotated for Statistical Reporting Purposes

Endnotes--page 72 - 47

- <u>1/</u> See 9903.88.03.
- 2/ See 9902.14.93.
- $\overline{3/}$ See 9903.88.15. Also see note 16 to subchapter III, chapter 99 and related tariff provisions for this duty treatment.
- 4/ See 9903.88.16. Also see note 16 to subchapter III, chapter 99 and related tariff provisions for this duty treatment.
- 5/ See 9903.88.49.
- 6/ See 9903.88.51 and 9903.88.57.
- <u>7/</u> See 9903.88.51.